

-1-

DESCRIPTION

AN IMAGE FORMATION APPARATUS

5 TECHNICAL FIELD

The present invention generally relates to an image formation apparatus, and especially relates to an image formation apparatus equipped with an ink drop discharging head.

10

BACKGROUND ART

[Patent reference 1] JP, 4-15735, B

[Patent reference 2] JP, 10-81012, A

An ink jet head for discharging an ink
15 drop is used by an ink jet recording device serving image formation apparatuses, such as printers, facsimile apparatuses, copiers, and plotters. As the ink jet head, products based on various technologies have been available, such as a piezo type product
20 wherein an ink drop is discharged by deforming a diaphragm that constitutes a partition of an ink passage (pressurized ink chamber) by a piezoelectric device serving as pressure generating means for generating pressure for pressurizing ink in the ink
25 passage such that the volume of the ink chamber is

-2-

changed, a thermal type product wherein an ink drop is discharged by generating air bubbles by heating the ink in the pressurized ink chamber using an exothermic resistor, and an electrostatic product
5 wherein an ink drop is discharged by changing the volume of the pressurized ink chamber by deforming a diaphragm by an electrostatic force applied between the diaphragm and an electrode that opposes the diaphragm.

10 For driving the ink jet head, there are two methods. Namely, one is called a "push and strike" method whereby an ink drop is discharged by reducing the volume of the pressurized ink chamber by pushing the diaphragm toward the pressurized ink
15 chamber, and a "pull and strike" method whereby an ink drop is discharged when the diaphragm that is first pulled out is made to return to its original position.

Further, a method of forming a large ink
20 drop is disclosed by Patent reference 1 wherein two or more minute ink drops, i.e., ink droplets, are sequentially discharged, and the ink droplets merge before reaching a recording medium (paper form) to form a large ink drop.

25 Furthermore, an apparatus that is capable

-3-

of gradation printing is disclosed by Patent
reference 2 wherein a first drive pulse discharges a
first ink drop, and a second drive pulse discharges
a second ink drop, dimensions of which are different
5 from the first ink drop; and more than four
gradation steps are made available by combining the
first and the second drive pulses.

[Problem(s) to be solved by the Invention]

Generally, large ink drops are used to
10 print a wide area, and small ink drops are used to
print a fine pattern. Accordingly, the large ink
drops need to contain sufficient ink volume that is
a function of the resolution defined by the pitch of
nozzles and the number of nozzle columns. For
15 example, two nozzle columns for the same color
having a nozzle pitch of 150 dpi provide a 300 dpi
resolution. If the ink volume of the large ink drops
is not sufficiently great, the wide area may not be
fully printed, leaving white spots in the nozzle
20 column directions (sub-scanning directions). This
requires interlacing, which slows down the printing
speed.

If the nozzle pitch is made finer, less
ink drop volume may be sufficient. However, this
25 poses problems, such as there being a limit in

-4-

reducing the nozzle pitch due to available process precision, the printing speed becoming slower unless the number of nozzles increases, and the cost increased due to the increased number of channels of control IC for controlling the increased number of nozzles.

For this reason, the volume of ink needed for large ink drops is still great. On the other hand, the small ink drops are required to be smaller for realizing a finer pattern to be printed. That is, the ratio of the ink drop volume M_j of the large ink drop to that of the small ink drop is increasing, and accordingly, it is required that the large ink drops and the small ink drops be distinctively controlled.

In order to solve the problems as mentioned above, the method for merging small ink drops before reaching the target medium (paper form) for obtaining a large ink drop as disclosed by [Patent reference 1] is desired to be improved such that the volume of the small ink drops can be reduced, and the number of the small ink drops for forming a large ink drop can be increased.

In addition, in order for the large ink drop to spread in the sub-scanning directions, the

-5-

small ink drops need to be merged before reaching the target medium (paper form), which requires that the small ink drops be discharged at short intervals such as microseconds. For example, if the gap
5 between the nozzle and the recording medium (paper form) is set at about 1 mm, and the speed of the ink drops V_j is considered to range between 5 and 10+ m/s, as usually practiced, the ink drops reach the target medium (paper form) in 100 - 200 μ s.

10 In this time interval, pressure vibration of the pressurized ink chamber due to discharging a preceding ink drop is not sufficiently damped. For this reason, the frequency at which ink drops are sequentially discharged needs to be at a proper
15 timing in reference to vibration of the pressurized ink chamber.

Here, the timing dependence when two ink drops are discharged is explained with reference to Fig. 39 and Fig. 40, wherein a piezoelectric device
20 (piezoelectric vibrator) that displaces in d33 directions constitutes a head.

Fig. 39 shows a drive pulse for discharging the two ink drops, the drive pulse containing two drive pulses P501 and P502. In the
25 case of the head using the piezoelectric device

-6-

(piezoelectric vibrator) displacing in the d33 directions as mentioned above, an ink drop is discharged when the pressurized ink chamber is contracted by a wave element P501a (rising inclination identified by an arrow) and a wave element P502a (rising inclination identified by an arrow) that are rising edges of the drive pulses P501 and P502, respectively.

Fig. 40 shows an example of measurements of the ink drop speed V_j and the ink drop volume M_j , when a time interval T_d of the ink discharge (discharge interval) between the two drive pulses P501 and P502 is varied. Here, the ink drop speed V_j is obtained based on the time from the discharge of the first ink drop to the arrival of the first ink drop at the target medium (paper form) that is 1 mm far. For this reason, the ink drop speed V_j when used for the second ink drop is slightly lower than actual. Further, plotted points that are shown only by black triangles (i.e., white triangles are not associated) indicate that the ink drop speed V_j of the first ink drop and the second ink drop are the same, and the second ink drop is merged with the first ink drop (the two ink drops have coalesced). Furthermore, the ink drop volume M_j is obtained from

-7-

the total of ink consumption after ink drops discharge for a given number of times, and is the sum of the first ink drop and the second ink drop in this example.

5 As seen from Fig. 40, in the cases of $T_d=8$ and $T_d=12$ wherein the properties (V_j and M_j) have a steep inclination, the ink drop speed V_j and the ink drop volume M_j tend to greatly change when the vibration frequency slightly shifts due to external
10 factors, such as variation of the head, temperature, and negative pressure, which change is not a desirable result. On the other hand, when T_d is near 10, pressures mutually cancel out, and the ink drop speed V_j tends to become low, which undesirably
15 causes the second ink drop to be unable to merge with the first ink drop.

That is, it is desirable to discharge ink drops at the timing where the pressures are in sync (peak timing).

20 However, as the number of ink drops that are to merge is increased, and the ink drops are sequentially discharged at the peak timing, the pressurized ink chamber is violently excited in terms of vibration. The vibration, i.e., residual
25 vibration, causes additional and unwanted ink to be

-8-

discharged. Since the additional ink is discharged with inappropriate pressure, the discharge is imperfect, causing the surface of the nozzle to become soiled. When the nozzle surface is soiled, direction of ink injection can to be bent (deflected from straight down), the nozzle may become clogged and incapable of squirting, the ink drop speed V_j may be decreased, and the discharge may be not make a drop but become a mist, resulting in poor printing.

10 To cope with this, i.e., in order that the residual pressure does not cause the discharge of additional and unwanted ink, it is often practiced that the driver voltage is lowered. However, when the number of ink drops increases, the voltage margin within which discharge can be stably carried out becomes narrow. That is, lowering the voltage is not always an answer.

DISCLOSURE OF THE INVENTION

20 It is a general object of the present invention to provide an image formation apparatus that substantially obviates one or more of the problems caused by the limitations and disadvantages of the related art.

25 A more specific object of the present

-9-

invention is to provide an image formation apparatus that can print a high-definition image at high speed, wherein the ink drop volume M_j is able to be varied over a wide range, while ink drop discharging is
5 stably carried out.

Features and advantages of the present invention are set forth in the description that follows, and in part will become apparent from the description and the accompanying drawings, or may be
10 learned by practice of the invention according to the teachings provided in the description. Objects as well as other features and advantages of the present invention will be realized and attained by the image formation apparatus particularly pointed
15 out in the specification in such full, clear, concise, and exact terms as to enable a person having ordinary skill in the art to practice the invention.

To achieve these and other advantages and
20 in accordance with the purpose of the invention, as embodied and broadly described herein, the invention provides as follows.

[Means for Solving the Problem]

The image formation apparatus according to
25 the present invention that solves the above problems

-10-

includes a structure for sequentially discharging a predetermined number of ink drops, wherein at least one ink drop other than the last ink drop of the multiple ink drops is discharged after its preceding
5 ink drop at an interval of about $(n+1/2) \times T_c$, where n is an integer equal to or greater than 1, and T_c represents resonance cycle of a pressurized ink chamber.

Here, it is desirable that n be set at 1
10 ($n=1$), i.e., the interval be set at $1.5 \times T_c$.
Further, as for ink drops other than one or more ink drops that are discharged at the intervals of $(n+1/2) \times T_c$ after their respective preceding ink drops, they are desirably discharged at an interval
15 of about $n \times T_c$ after their respective preceding ink drops.

Further, the first ink drop is desirably discharged by contracting, but without first expanding, the pressurized ink chamber, or
20 alternatively, by contracting the pressurized ink chamber by a volume greater than a first expanding volume. In this case, it is desirable that the second ink drop be discharged at the interval of about $(n+1/2) \times T_c$ after the first ink drop. The ink
25 drop speed V_j is calculated by the time duration of

-11-

a discharged ink drop reaching the target medium (paper form), which distance is set to be 1 mm, assuming that there are no more ink drops following.

Furthermore, the ink drop speed V_j of ink drops discharged at intervals of about $(n+1/2) \times T_c$ after respective preceding ink drops is desirably set to be greater than 3 m/s, at which speed sequential ink drops are able to merge.

Furthermore, it is desirable that four or more ink drops merge to form one ink drop during flight from the nozzle to the target medium.

Further, it is desirable that the drive pulse include a waveform for suppressing the residual vibration after the drive pulse for discharging the last ink drop. In this case, the waveform for suppressing the residual vibration is desirably shaped such that the vibration is damped within the resonance cycle T_c after discharging the last ink drop.

Furthermore, it is desirable that a selected part(s) of the drive pulse for forming a large ink drop be capable of forming a small-sized ink drop and a medium-sized ink drop. Further, it is desirable that the drive pulse include a waveform that vibrates a meniscus, yet without making an ink

-12-

drop discharge. Further, it is desirable that there be an interval wherein a voltage is applied to pressure generating means even if a given channel does not discharge an ink drop in a given printing
5 cycle. In this case, it is desirable that the pressure generating means be a piezoelectric device, and the piezoelectric device be recharged during the interval where the above-mentioned voltage is applied.

10 Here, a piezoelectric device, the displacement direction of which is d33, can serve as the pressure generating means. Further, support sections of the piezoelectric device, which support sections correspond to partitions of the pressurized
15 ink chambers, can be a part of the piezoelectric device.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a perspective diagram showing an
20 example of a mechanism section of an ink jet recording device serving as an image formation apparatus of the present invention.

Fig. 2 is a side view of the mechanism section of the ink jet recording device.

25 Fig. 3 is a cross-sectional view showing

-13-

an example of an ink jet head that constitutes a recording head of the recording device taken along the direction of the longer side of a ink chamber.

Fig. 4 is a cross-sectional diagram
5 showing the ink jet head taken along the shorter side of the ink chamber.

Fig. 5 is a block diagram showing the outline of a control unit of the ink jet recording device.

10 Fig. 6 is a block diagram showing a portion of the control unit concerning drive control of the ink jet head.

Fig. 7 is a graph showing a drive signal according to the first embodiment of the present
15 invention.

Fig. 8 is a graph showing the drive signal of a first comparative example.

Fig. 9 is a graph for explaining relations between ink drop speed and voltage in the cases of
20 the first embodiment and the first comparative example.

Fig. 10 is a graph for explaining relations between ink drop volume and voltage in the cases of the first embodiment and the first
25 comparative example.

-14-

Fig. 11 shows ink drop discharging situations corresponding to the drive pulse of the first embodiment.

Fig. 12 shows ink drop discharging situations corresponding to the drive pulse of the first comparative example.

Fig. 13 graphs frequency characteristics of the ink drop speed in the cases of the first embodiment and the first comparative example.

Fig. 14 graphs frequency characteristics of the ink drop volume in the cases of the first embodiment and the first comparative example.

Fig. 15 graphs frequency characteristics of the ink drop speed for the same ink drop volume in the cases of the first embodiment and the first comparative example.

Fig. 16 graphs frequency characteristics of the ink drop volume for the same ink drop speed in the cases of the first embodiment and the first comparative example.

Fig. 17 shows ink drop discharging situations corresponding to the drive pulse of the first embodiment.

Fig. 18 shows ink drop discharging situations corresponding to the drive pulse of the

first comparative example.

Fig. 19 graphs the drive signal according to the second embodiment of the present invention.

Fig. 20 graphs voltage characteristics of the drive pulse according to the second embodiment.

Fig. 21 graphs the drive signal according to the third embodiment of the present invention.

Fig. 22 graphs the drive signal according to the fourth embodiment of the present invention.

Fig. 23 graphs the drive signal according to the fifth embodiment of the present invention.

Fig. 24 graphs the drive signal according to the sixth embodiment of the present invention.

Fig. 25 graphs relations between the ink drop volume and the number of pulses corresponding to the drive pulse according to the first embodiment.

Fig. 26 graphs relations between the ink drop volume and ink drop speed corresponding to the drive cycle of the drive pulse according to the first embodiment.

Fig. 27 graphs a voltage waveform of the drive pulse for discharging the second ink drop.

Fig. 28 graphs a voltage waveform of the drive pulse for discharging the second ink drop.

Fig. 29 graphs the drive signal according

to the seventh embodiment of the present invention.

Fig. 30 graphs the drive signal according to the eighth embodiment of the present invention.

Fig. 31 graphs the drive signal according to the ninth embodiment of the present invention.

Fig. 32 is an expanded view of Fig. 31.

Fig. 33 graphs the drive pulse for explaining gradation recording.

Fig. 34 graphs the drive pulse for forming a large ink drop.

Fig. 35 graphs the drive pulse for forming a middle-sized ink drop.

Fig. 36 graphs the drive pulse for forming a small ink drop.

Fig. 37 graphs a voltage waveform applied to a non-discharging channel.

Fig. 38 graphs a voltage waveform for generating meniscus vibration applied to a non-discharging channel.

Fig. 39 graphs a voltage waveform for discharging two ink drops.

Fig. 40 graphs timing characteristics in the case of discharging two ink drops.

-17-

BEST MODE FOR CARRYING OUT THE INVENTION

In the following, embodiments of the present invention are described with reference to the accompanying drawings.

5 Fig. 1 is a perspective diagram showing a mechanism section of an ink jet recording device serving as an image formation apparatus of the present invention. Fig. 2 is a side view of the mechanism section of the ink jet recording device.

10 The ink jet recording device includes a recording device main part 1 that includes a printing mechanism unit 2 that further includes a carriage 13 that is movable in the main scanning direction, one or more ink jet heads 14 mounted to
15 the carriage 13, and one or more ink cartridges 15 for supplying ink to the ink jet heads 14. The ink jet recording device further includes a feed cassette 4, and optionally includes a hand feeding tray 5, for supplying a recording medium (paper
20 form) 3 such that a desired image is printed thereon by the printing mechanism unit 2, and a delivery tray 6 provided on the rear side of the ink jet recording device for delivering the recording medium
3.

25 The printing mechanism unit 2 includes a

-18-

main guide rod 11 and a sub-guide rod 12, both
serving as a guiding member prepared horizontally
across side plates provided (not illustrated) on the
right and left sides, the guiding member supporting
5 the carriage 13 so as to be sliding-free in the main
scanning direction (i.e., perpendicular to the paper
of Fig. 2). Each of the ink jet heads 14 discharges
one of yellow (Y), cyan (C), magenta (M), and black
(Bk) inks, with the direction of ink drop discharge
10 being set downward. The ink cartridges 15 are
provided in the upper part of the carriage 13 for
supplying respective inks to the ink jet heads 14,
the ink cartridges 15 being replaceable.

Each of the ink cartridges 15 includes an
15 atmospheric mouth prepared at the upper part for
free passage of the air, an ink supply mouth
prepared at the bottom part for supplying ink, and a
porous material-containing object that is filled up
with ink wherein the ink to be supplied to the ink
20 jet head 14 is maintained at a slightly negative
pressure by the capillary tube action of the porous
material. Ink is supplied to the ink jet heads 14
from respective ink cartridges 15.

As briefly described above, the carriage
25 13 is installed sliding-free with its rear side

-19-

inserted into the main guide rod 11, the rear side being on the down stream side of the recording medium 3 (paper form) being conveyed, and with its front side being placed on the sub-guide rod 12, the front side being on the upper stream side of the recording medium 3 being conveyed. In order to move the carriage 13 for scanning in the main scanning direction, a timing belt 20 is installed between a drive pulley 18 and a follower pulley 19 that are driven by a main scanning motor 17. The timing belt 20 is fixed to the carriage 13 such that the carriage 13 moves to and fro as the rotation of the main scanning motor 17 is reversed.

Further, although one of the ink jet heads 14 is provided as the recording head for each color here, one head having multiple nozzles for discharging ink drops in each color can also be used. In the present embodiment, piezoelectric type ink jet heads are used as the ink jet heads 14, each of which includes a diaphragm that forms at least a part of the surface of an ink passage partition, wherein a piezoelectric device deforms the diaphragm.

In order to convey the recording medium (paper form) 3 set to the feed cassette 4 to the lower part side of the head 14, the printing

-20-

mechanism unit 2 includes a feed roller 21 and a friction pad 22 for separating and feeding a sheet of the paper form 3 from the feed cassette 4, a guide member 23 for guiding the paper form 3, a conveyance roller 24 for conveying the paper form 3 in the reverse direction, a conveyance pinch roller 25 pushed to the circumference of the conveyance roller 24, a tip pinch roller 26 for defining the conveyance angle of the paper form 3 conveyed by the conveyance roller 24, and a sub-scanning motor 27 for rotating the conveyance roller 24 through a gear sequence.

The printing mechanism unit 2 further includes a paper form receiving member 29 for guiding the paper form 3 conveyed by the conveyance roller 24 corresponding to the moving range in the main scanning direction of the carriage 13 at the lower part of the ink jet heads 14. The printing mechanism unit 2 further includes the following items on the downstream side of the paper form conveyance of the paper form receiving member 29, namely, a conveyance pinch roller 31 and a spur 32 that rotate for conveying the paper form 3 in the delivery direction, a delivery roller 33 and a spur 34 for delivering the paper form 3 to the delivery

-21-

tray 6, and guide members 35 and 36 for forming a delivery path.

With the configuration as described above, printing a line is carried out by moving the carriage 13 in the main scanning direction, by driving the ink jet heads 14 according to an image signal, and by discharging corresponding inks onto the paper form 3 that is stopped. When printing of the line is completed, the following line is printed after conveying the paper form 3 by a predetermined amount. When one of a print end signal and a signal indicating that the paper form 3 has arrived at a predetermined bottom of the print area is received, printing is terminated and the paper form 3 is delivered.

Further, in a position outside of the printing area on the right-hand side of the moving direction of the carriage 13, a recovery apparatus 37 for recovering from poor discharging of the ink jet heads 14 is arranged. The recovery apparatus 37 is equipped with cap means, suction means, and cleaning means. While the carriage 13 is not being used, it is moved to the recovery apparatus 37, and the capping means caps the ink jet heads 14 such that a moist state of the nozzles is maintained, and

-22-

poor discharge due to ink dryness is prevented from occurring; and ink that is not related to printing is pumped out (purged) such that ink viscosity of all nozzles is adjusted for obtaining stable
5 discharging performance.

When poor discharging occurs, the capping means seals the nozzle of the ink jet head 14, the suction means evacuates ink, air bubbles, etc., out of the nozzle through a tube, and the cleaning means
10 removes ink, dust, etc., adhering to the nozzle. In this manner, adequate discharging is restored. Further, the evacuated ink is exhausted to an ink disposal tank (not illustrated) installed in the lower part of the main part 2, and an ink absorber
15 arranged in the ink disposal tank absorbs the disposed ink.

Next, descriptions follow about the ink jet heads 14 of the ink jet recording device with reference to Fig. 3 and Fig. 4. Here, Fig. 3 is a
20 cross-sectional diagram of the ink jet heads 14 in the longer side direction of the ink chamber, and Fig. 4 is a cross-sectional diagram of the ink chamber of the ink jet heads 14 in the shorter side direction.

25 The ink jet heads 14 include a passage

-23-

board 41 formed by a single-crystal-silicon substrate, a diaphragm 42 joined to the undersurface of the passage board 41, and a nozzle plate 43 joined to the upper surface of the passage board 41, which constitute a pressurized ink chamber 46 for forcing the ink through a nozzle passage 45a such that a nozzle 45 discharges an ink drop, and an ink supply way 47 serving as a fluid-resistance section for supplying ink to the pressurized ink chamber 46 from a common ink chamber 48 to which the ink is supplied from an ink supply mouth 49.

Further, a laminated type piezoelectric device 52 serving as an electro-mechanical transducer, i.e., pressure generating means (actuator means) for pressurizing the ink in the pressurized ink chamber 46 is provided on the external surface side (the side opposite to the pressurized ink chamber side) of the diaphragm 42 corresponding to each pressurized ink chamber 46. The piezoelectric device 52 is joined to a base substrate 53. Further, in the piezoelectric device 52, support sections 54 are formed corresponding to partition sections 41a that separate the pressurized ink chambers 46 (bi-pitch structure). Here, a slit process of half-cut dicing is carried out such that

-24-

the piezoelectric device is divided like the shape of comb teeth, adjacent teeth alternately serving as the piezoelectric device 52 and the support section 54. Although the support section 54 is materially and structurally the same as the piezoelectric device 52, the difference is that a driver voltage is not applied to the support section 54. In this manner, the support section 54 serves as a mere physical support.

10 Further, the perimeter of the diaphragm 42 is joined to a frame member 44 with an adhesive 50 that contains gap-filling material. The frame member 44 includes a concavity serving as the common ink chamber 48, and an ink supply hole, which is not
15 illustrated, for supplying ink to the common ink chamber 48 from the exterior. The frame member 44 is formed by injection molding with, for example, epoxy system resin or polyphenylene sulfide.

Here, although the passage board 41 is
20 formed by anisotropic etching of, for example, a single-crystal silicon substrate of a crystal-face direction (110) using an alkaline etching solution, such as potassium-hydroxide solution (KOH), for forming the concavity and the hole section serving
25 as the nozzle passage 45a, the pressurized ink

-25-

chamber 46, and the ink supply way 47, other materials can be used, such as stainless steel substrates, photosensitive resins, etc.

Although the diaphragm 42 is formed, for example, from a metal plate of nickel by an electroforming method, other materials may be used, such as other metal plates, a resin board, combined materials of metal and resin, and the like. The diaphragm 42 constitutes a thin part 55 (diaphragm section) for making deformation easy in the portion corresponding to the pressurized ink chamber 46, and a thick part 56 (in the shape of an island) for joining to the piezoelectric device 52. Further, at the portion corresponding to the support section 54 and the joint section to the frame member 44, a thick part 57 is formed. The flat side of the diaphragm 42 is fixed to the passage board 41 with an adhesive, and the thick part 56 is fixed to the piezoelectric device 52 with an adhesive. The thick part 57 is fixed to the support section 54 and the frame member 44 with adhesives 50. Here, the diaphragm 42 is constituted by a nickel plating layer formed by electroforming, and the like, wherein thickness of the thin part (diaphragm section) 55 is set to 3 μ m, and width is set to 35

-26-

„m (one side) .

The nozzle plate 43 includes the nozzle 45 having a diameter of 10 through 35 „m corresponding to each pressurized ink chamber 46, and adhesively
5 fixed to the passage board 41. As the nozzle plate 43, various materials can be used, such as stainless steel and nickel, combinations of metal and resin such as a polyimide resin film, silicon, and combinations thereof. Here, the nozzle plate 43 is
10 formed by a nickel plating film prepared by the electroforming method, and the like. Further, the internal shape (inner side form) of the nozzle 43 is shaped like a horn (alternatively, a shape near to a cylinder, and a shape near to a right circular cone),
15 and the diameter of the nozzle 45 is set to about 20-35 „m at the ink drop outlet side. Furthermore, the nozzle pitch of each nozzle sequence is set at 150 dpi.

Further, on the nozzle surface (surface in
20 the ink discharging direction) of the nozzle plate 43, a water-repellent finish layer (not illustrated) is prepared. The water-repellent-finish layer can be formed in various manners such as PTFE-nickel eutectoid plating, electro-deposition painting of
25 fluororesin, evaporation-coating of fluororesin with

-27-

evaporability such as fluoride pitch, and baking after application of a solvent of silicon system resin and fluorine system resin. An adequate water-repellent finish layer is selected depending on
5 physical properties of the ink such that the ink drop formation, and the ink flight property, for example, are stabilized in order obtain high-definition image quality.

The piezoelectric device 52 is constituted
10 by laminating piezo-electric layers 61 of lead zirconate titanate (PZT), the thickness of each layer being 10-50 μ m, and internal electrode layers 62 of silver-palladium (AgPd), thickness of each layer being several micrometers, wherein the
15 internal electrodes 62 are electrically connected to individual electrodes 63 and a common electrode 64 alternately. The individual electrodes 63 and the common electrode 64 are terminal electrodes (external electrode) provided on the edges. With the
20 arrangement described above, the pressurized ink chamber 46 is contracted and expanded by expansion and contraction, respectively, of the piezoelectric device 52 having a piezoelectric constant of d33. When a drive pulse is applied to the piezoelectric
25 device 52, the piezoelectric device 52 is charged

-28-

and expands; when the charge is removed, the piezoelectric device 52 contracts.

The terminal electrodes on a side of the piezoelectric device 52 are divided by a half-cut
5 dicing process to form the individual electrodes 63, while, on the other hand, the terminal electrodes on the other side are not divided, and the common electrode 64 is formed, the common electrode 64 being electrically connected to all the
10 piezoelectric devices 52.

In order to provide a drive pulse to the individual electrodes 63 of the piezoelectric device 52, an FPC cable 65 is connected to the individual electrodes 63 by one of solder junction, ACF
15 (anisotropic conductivity film) junction, and wire bonding, and the other end of the FPC cable 65 is connected to a drive circuit (driver IC) such that the drive pulse is selectively applied to each piezoelectric device 52. Further, the common
20 electrode 64 is connected to the ground (GND) electrode of the FPC cable 65.

According to the ink jet head configured as above, when a drive pulse having a voltage of, for example, 10-50 V is applied to the piezoelectric
25 device 52 according to a print signal, a

-29-

displacement occurs in the direction of the layers of the piezoelectric device 52, i.e., in the d33 direction according to the present embodiment, the ink in the pressurized ink chamber 46 is pressurized
5 through the diaphragm 42, the pressure of the ink rises, and an ink drop is discharged from the nozzle 45.

Then, with the end of ink discharge, the ink pressure in the pressurized ink chamber 46
10 decreases, and negative pressure occurs in the pressurized ink chamber 46 due to the inertia of the ink flow and the electric discharge process of the drive pulse, and an ink filling process starts. At this time, the ink supplied from the ink tank which
15 is not illustrated flows into the common ink chamber 48, and passes along the fluid-resistance section 47 through the ink supply mouth 49 from the common ink chamber 48, and the pressurized ink chamber 46 is filled with ink.

20 In addition, while the fluid-resistance section 47 has an effect in damping of the residual pressure vibration after discharging, it serves as a resistor to refilling due to surface tension. Accordingly, by suitably selecting the fluid-
25 resistance value of the fluid-resistance section 47,

-30-

the balance between damping of the residual pressure and refill time can be selected so that the drive cycle, i.e., the time between a discharge and the next discharge can be shortened.

5 Next, an outline of the control unit of the ink jet recording device is explained with reference to Fig. 5 and Fig. 6. Here, Fig. 5 is a block diagram showing the outline of the control unit, and Fig. 6 is a block diagram showing a
10 portion concerning head drive control of the control unit.

 The control unit includes a printer controller 70, a motor driver 81 for driving the main scanning motor 17 and the sub-scanning motor 27,
15 and a head driver 82 for driving the ink jet heads 14, the head driver 82 consisting of a head drive circuit, a driver IC, etc.

 The printer controller 70 includes an interface (I/F) 72 for receiving printing data from
20 a host computer and the like through a cable and/or a network, a main control unit 73 consisting of a CPU and the like, RAM 74 for storing data, ROM 75 for storing routines for data processing, an oscillation unit 76, a drive signal generating unit
25 77 serving as drive pulse generating means for

-31-

generating drive pulses for the ink jet heads 14, an I/F 78 for sending printing data in the form of dot-pattern data (bit map data), drive pulses, etc., to the head driver 82, and an I/F 79 for sending motor
5 drive data to the motor driver 81.

The RAM 74 serves as various buffers, working memory, etc. The ROM 75 stores various control routines performed by the main control unit 73, font data, graphic functions, various processes,
10 etc.

The main control unit 73 reads the printing data in a receiving buffer included in the I/F 72, and converts the data into intermediary codes. The intermediary codes are stored in an
15 intermediary buffer constituted by a predetermined area of the RAM 74, and are converted to dot-pattern data using font data stored in the ROM 75. The dot-pattern data are stored in a different predetermined area of the RAM 74. In the case that the printing
20 data are converted to bit map data by a printer driver of a host computer, the RAM 74 simply stores the printing data in the bit map format with no need for the conversion as described above.

With reference to Fig. 6, the main control
25 unit 73 then provides 2-bit gradation signals 0 and

-32-

1 according to the printing data, a clock signal CLK,
a latch signal LAT, and control signals MN0 through
MN3 to the head driver 82.

As shown in Fig. 6, the drive signal
5 generating unit 77 includes an amplifier 92 and a
wave generation unit 91. The wave generation unit 91
contains a ROM, which ROM function may be served by
a part of the ROM 75, for storing pattern data of a
drive pulse Pv, and a D/A converter for carrying out
10 digital-to-analog conversion of the drive pulse data
read from the ROM.

The head driver 82 includes a shift
register 103 for inputting the gradation signal 0
and the clock signal CLK from the main control unit
15 73, a shift register 104 for inputting the gradation
signal 1 and the clock signal CLK from the main
control unit 73, a latch circuit 105 for latching a
register value of the shift register 103 by the
latch signal LAT from the main control unit 73, a
20 latch circuit 106 for latching a register value of
the shift register 104 by the latch signal LAT from
the main control unit 73, a selector 107 for
selecting one of the control signals MN0 through MN3
from the main control unit 73 based on an output
25 value of the latch circuit 105, and an output value

-33-

of the latch circuit 106, a level conversion circuit (level shifter) 108 for receiving the output of the selector and for changing the level of the output value from the selector 107, and an analog switch array (switch means) 109, ON/OFF state of which is controlled by the level shifter 108.

The switch array 109 consists of an array of the switches AS1 through ASm to which the drive pulse Pv is provided from the drive signal generating unit 77. Each of the switches AS1 through ASm is connected to one of the piezoelectric devices 52 corresponding to one of the nozzles of one of the recording heads (ink jet head) 14.

The 2-bit gradation signals 0 and 1 serially transmitted from the main control unit 73 are latched by the latch circuits 105 and 106 at the beginning of a printing cycle, and selected ones of the switches AS1 through ASm of the switch array 109 are turned on according to a control signal selected from the control signals MN0 through MN3, the control signal selection being based on the gradation data.

While the corresponding one of the switches AS1 through ASm of the switch array 109 is turned on, the drive pulse Pv is applied to the

-34-

piezoelectric device 52, and the piezoelectric device 52 expands and contracts according to the drive pulse. On the other hand, while the corresponding one of the switches AS1 through ASm is
5 turned off, supply of the drive pulse to the piezoelectric device 52 is interrupted. Here, the signal provided to the switches AS1 through ASm is called the "drive pulse", and the signal that is applied to the piezoelectric device 52 is called the
10 "drive signal".

Here, the shift registers 103 and 104 and latch circuits 105 and 106 are constituted by logic circuits, and the level conversion circuit 108 and the switching circuit 109 are constituted by analog
15 circuits. Further, the circuit arrangement for switching the switch means based on the gradation signal (gradation data) is not limited to the above-mentioned configuration, but any configuration that can turn on/off a desired switch can be used.

20 Next, the details of the first embodiment of the present invention are explained with reference to Fig. 7 through Fig. 18. First, Fig. 7 shows the drive pulse according to the first embodiment of the present invention, the drive pulse
25 being the same as the drive signal in the first

-35-

embodiment. The drive pulse includes a first drive pulse P1, a second drive pulse P2, a third drive pulse P3, and a fourth drive pulse P4 that are output serially (sequentially) in time. At the
5 rising period indicated by a, each drive pulse makes the pressurized ink chamber 46 contract, and makes an ink drop be discharged.

According to the first embodiment, the time interval (discharge interval) between a first
10 ink drop discharged by the first drive pulse P1 and a second ink drop discharged by the second drive pulse P2 is set at $1.5 \times T_c$, the time interval (discharge interval) between the second ink drop discharged by the second drive pulse P2 and a third
15 ink drop discharged by the third drive pulse P3 is set at $1.5 \times T_c$, and the time interval (discharge interval) between the third ink drop discharged by the third drive pulse P3 and a fourth ink drop discharged by the fourth drive pulse P4 is set at 2
20 $\times T_c$. Here, T_c represents the specific vibration cycle of the pressurized ink chamber 46.

For comparison, a first comparative example is provided. The drive pulse of the first comparative example is as shown in Fig. 8. The first
25 comparative example includes a drive pulse P101, a

-36-

drive pulse P102, and a drive pulse P103 that are output serially in time. These drive pulses make the pressurized ink chamber 46 contract at the pulse rising period indicated by a, and make ink drops be discharged. As seen, the pulse rising period a of the drive pulse P101 is the same as that of the drive pulse P1 of the first embodiment, the drive pulse P2 of the first embodiment is eliminated, (i.e., the pulse rising period a of the drive pulse P2 is not present in the first comparative example), the drive pulse P102 is the same as the drive pulse P3, and the drive pulse P103 is the same as the drive pulse P4.

Accordingly, as for the first comparative example, the time interval between the first ink drop discharged by the drive pulse P101 and the second ink drop discharged by the drive pulse P102 is nearly equal to $3T_c$ (i.e., $1.5T_c \times 2$), and the time interval between the second ink drop discharged by the drive pulse P102 and the third ink drop discharged by the drive pulse P103 is nearly equal to $2T_c$.

Then, ink drop discharge was experimented with using the drive pulse of the first embodiment and the drive pulse of the first comparative example.

-37-

The results are shown in Fig. 9 and Fig. 10. In Fig. 9, the results of the ink drop speed V_j (vertical axis) corresponding to the maximum voltage of the drive pulse (horizontal axis) are shown. In Fig. 10, the results of the ink drop volume M_j (vertical axis) corresponding to the maximum voltage of the drive pulse (horizontal axis) are shown. For the purposes of Fig. 9 and Fig. 10, the drive pulse wave forms in Fig. 7 and Fig. 8 were similarly transformed, i.e., gain adjustments were carried out. Further, repetition frequency was set to 8 kHz. Here, the solid line in each of Fig. 9 and Fig. 10 shows the results of the first embodiment, and the dashed line shows the results of the first comparative example.

As shown in Fig. 9 and Fig. 10, in the case of the first comparative example, ink drop discharge became unstable at the driver voltage of 22 V. Although the vertical value for 22 V is shown as being zero, this does not mean that there was no discharge, but the discharge was unstable, and measurement of an exact numeric value was impossible. This unstable discharge was determined to be due to the surface of the nozzle being dirty, which was caused by a meniscus significantly rising due to the

-38-

residual pressure (or a very slow discharge speed) after discharge of the last ink drop (the third ink drop), and the ink was not drawn back into the nozzle.

5 On the other hand, in the case of the drive pulse of the first embodiment, even if the driver voltage was increased to 24 V, ink drop discharge was not disturbed. Further, for the same voltages, the drive pulse of the first embodiment
10 discharged a greater ink drop volume M_j than the first comparative example, although four ink drops were discharged according to the first embodiment.

That is, the first embodiment more stably discharged a large ink drop. Since the time from the
15 first discharge to the last discharge was the same, the large ink drop was obtained with no additional time required, and it was easy for the last ink drop to merge with the first ink drop.

Fig. 11 shows a discharge state in the
20 case of the first embodiment. Fig. 12 shows a discharge state in the case of the first comparative example. Here, the maximum voltage of the drive pulse of the first embodiment was set at 16.9 V, and the maximum voltage of the first comparative example
25 was set at 15.3 V, both voltages being determined

-39-

based on the characteristics shown by Fig. 9 such that the same ink drop speed of $V_j=7$ m/s was obtained in both cases. Using a stroboscope, the situation near the nozzle was observed 80 μ s after
5 the drive signal was generated. Here, the repetition frequency was set at 4 kHz.

The difference between Fig. 11 and Fig. 12 is that a meniscus M due to the residual pressure vibration was visibly present after discharge in Fig.
10 12 (the first comparative example), while there was no meniscus observed in the case of the first embodiment. This provides evidence that the drive pulse of the first embodiment successfully suppressed the residual pressure vibration.

15 The residual pressure vibration also affected frequency characteristics of discharging. Fig. 13 and Fig. 14 show the frequency characteristics, the ink drop speed V_j and the ink drop volume M_j , respectively, according to the drive
20 pulse of the first embodiment and the first comparative example. In Fig. 13 the vertical axis represents the ink drop speed V_j , and in Fig. 14 the vertical axis represents the ink drop volume M_j . The horizontal axes of Fig. 13 and Fig. 14 represent the
25 repetition cycle T . Here, the maximum voltage of the

-40-

drive pulse of the first embodiment was set at 16.9 V, and the maximum voltage of the first comparative example was set at 15.3 V, both voltages being determined based on the characteristics shown by Fig. 9 such that the same ink drop speed of $V_j=7$ m/s was obtained in both cases. Further, the solid line shows the result of the first embodiment, and the dashed line shows the result of the first comparative example.

As seen from Fig. 13, the drive pulse of the first embodiment provided better flatness of the ink drop speed V_j than the first comparative example. This indicates that where the residual pressure was small, the influence of the repetition cycle becoming short on the discharging characteristics was small. Further, that the frequency characteristic of the ink drop speed V_j was flat means that an impact position (where the ink drop arrives on the recording medium) did not fluctuate with an image pattern, and that discharge stability was improved.

Further, as seen from Fig. 14, there was no significant difference between the first embodiment and the first comparative example as for the range of fluctuation (ΔM_j) of the frequency

-41-

characteristics of the ink drop volume M_j .
Nevertheless, the drive pulse of the first
embodiment discharged a greater amount of the ink
than the drive pulse of the first comparative
5 example.

Next, Fig. 15 and Fig. 16 show the
frequency characteristics when the maximum voltage
of the first comparative example was raised to 18.5
V so that the ink drop volume M_j became the same as
10 that of the first embodiment. In Fig. 15, the
vertical axis represents the ink drop speed V_j , and
in Fig. 16 the vertical axis represents the ink drop
volume M_j . Here, the data of the drive pulse of the
first embodiment in Fig. 15 and Fig. 16 are the same
15 as the data identified by "Vj: FIRST EMBODIMENT" in
Fig. 13 and Fig. 14, respectively.

As clearly seen from Fig. 15 and Fig. 16,
when the ink drop volume M_j to be discharged was
equalized, the fluctuation of the ink drop speed V_j
20 of the first comparative example became greater than
before (when the applied voltage was 15.3 V, i.e.,
in the case of Fig. 13), and the drive pulse of the
first embodiment provided the smaller range of
fluctuation ΔM_j of the ink drop volume M_j .

25 The mechanism of the first embodiment is

-42-

explained with reference to Fig. 17 and Fig. 18 that show the discharge state of the ink drops according to the drive pulse of the first embodiment and the drive pulse of the first comparative example, respectively. Here, the maximum voltage of the drive pulse of the first embodiment was set at 16.9 V, and the maximum voltage of the first comparative example was set at 15.3 V, both voltages being determined based on the characteristics shown by Fig. 9 such that the same ink drop speed of $V_j=7$ m/s was obtained in both cases. The stroboscope method was used to observe the situation near the nozzle 43 μ s after the drive signal was generated. Here, the timing, i.e., 43 μ s, is when the last ink drop began to be discharged from the nozzle.

In the case of the first embodiment, the second ink drop and the third ink drop had not reached the first ink drop as shown in Fig. 17. On the other hand, in the case of the first comparative example, the second ink drop had merged with the first ink drop as shown in Fig. 18. That is, in the case of the drive pulse of the first embodiment, discharging at the $1.5T_c$ intervals causes the residual pressure and the discharge pressure to cancel each other, and the speed of the second ink

-43-

drop and the third ink drop became slower.

Nevertheless, it is important that discharging be correctly carried out even if the speed is low.

Here, if the voltage of the drive pulse is
5 made lower, like the so-called damping wave, in an attempt to suppress the residual pressure vibration after the first ink drop, sufficient effect is not achieved. Rather, by generating a pressure that can cause the second ink drop to be correctly discharged,
10 the effect as in this embodiment is achieved.

Further, since the last ink drop (the fourth ink drop) needs to gather in the second and the third ink drops that travel at a slow speed, and merge with the first ink drop, the last ink drop has
15 to be discharged at an $n \times T_c$ interval with the preceding ink drop, not at an $(n+1/2) \times T_c$ interval. According to the present embodiment, for the last ink drop, the $n \times T_c$ interval is used and ink drop speed is made higher.

20 As described above, when multiple ink drops are to be sequentially discharged, ink drops other than the last ink drop are discharged at intervals nearly equal to $(n+1/2) \times T_c$ (where, n is an integer equal to or greater than 1) in order to
25 suppress the pressure vibration of the pressurized

-44-

ink chamber, and the last ink drop is discharged at an interval nearly equal to $n \times T_c$ in order to form a large ink drop.

In this manner, a subsequent ink drop can
5 be discharged earlier than before (with no need to wait for decay of the residual pressure due to the preceding ink drop), and the time required to form a large ink drop can be shortened, resulting in high printing speed. Further, since the time from the
10 first ink drop to the last ink drop is shortened, it is easy for the last ink drop to merge with the preceding ink drops, which merging suppresses the speed of the last ink drop. In this manner, a satellite SATE (unconverged ink drop) (see FIGS. 15
15 and 17) that otherwise reaches the recording medium later than a main drop can now reach the recording medium after merging.

In this case, the ink drop formation time can be further shortened by making $n=1$, i.e.,
20 causing the ink drop to be discharged at an interval nearly equal to $1.5 \times T_c$ after the preceding ink drop, the interval suppressing the pressure vibration.

Further, ink drops other than ink drops
25 that are discharged at intervals nearly equal to

-45-

($n+1/2$) \times T_c from the corresponding preceding ink drops are discharged at intervals of nearly equal to $n \times T_c$ from the corresponding preceding ink drops. Since the interval $n \times T_c$ is in sync with the peak
5 of the pressure vibration, variances of the discharge characteristics, i.e., V_j and M_j , due to a variation in the head, and a specific vibration cycle shift due to an external cause can be minimized.

10 In this manner, i.e., by providing ink drops discharged at intervals of nearly equal to ($n+1/2$) \times T_c from the preceding ink drop, except for the last ink drop, the pressure vibration of the pressurized ink chamber is prevented from becoming
15 excessive.

In addition, although the piezoelectric vibrator displacing in the d33 directions is used as the actuator of the ink jet head, other actuators can be used such as a piezoelectric vibrator
20 displacing in d31 directions.

However, it is desirable that the specific vibration cycle T_c be short such that two or more ink drops can easily merge, and the passage board constituting the pressurized ink chamber can be
25 firmly held. That is, as for the head structure, the

-46-

so-called bi-pitch structure is desirable wherein comb-like sliced portions of the actuator that are not driven support the partitions of the pressurized ink chamber.

5 In addition, it is more desirable that the piezoelectric device as the actuator be capable of quick response, and for this reason, the piezoelectric device should be structured with a low profile. For this purpose, it is desirable that the
10 actuator use a piezoelectric device that displaces in the d33 directions, because the piezoelectric constant is greater with d33 than d31.

 Next, the drive pulse according to the second embodiment of the present invention is
15 explained with reference to Fig. 19 and Fig. 20. The drive pulse of the second embodiment is designed such that the interval between the first ink drop discharged by the driving pulse P1 and the second ink drop discharged by the driving pulse P2 is set
20 at $1.5T_c$, the interval between the second pulse discharged by the driving pulse P2 and the third ink drop discharged by the driving pulse P3 is set at $2T_c$, and the interval between the third pulse discharged by the driving pulse P3 and the fourth
25 ink drop discharged by the driving pulse P4 is set

-47-

at $2T_c$. The voltage characteristics of the second embodiment are shown in Fig. 20. In addition, the head structure is the same as that of the first embodiment.

5 In this drive pulse, the second ink drop is discharged at the $1.5T_c$ interval from the first ink drop, which works such that the second ink drop cancels the residual pressure vibration. To the contrary, the third ink drop and the fourth ink drop
10 are discharged at intervals of $2T_c$ to the respective preceding ink drops, which intervals tend to increase the residual pressure vibration, and indeed a meniscus after discharge was slightly visible as compared with the first embodiment. However, the
15 discharge did not become unstable, even when the driver voltage was raised to 24 V as shown in Fig. 20. Further, the ink drop volume M_j of the second embodiment was greater than the first embodiment at the same voltages.

20 Next, the drive pulse according to the third embodiment of the present invention is explained with reference to Fig. 21. The drive pulse of the third embodiment is designed such that the interval between the first ink drop discharged by
25 the driver pulse P_1 and the second ink drop

discharged by the driver pulse P2 is set to $2T_c$, the interval between the second ink drop discharged by the drive pulse P2 and the third ink drop discharged by the drive pulse P3 is set to $1.5 T_c$, and the

5 interval between the third ink drop discharged by the drive pulse P3 and the fourth ink drop discharged by the drive pulse P4 is set to $2T_c$. Here, the head structure is the same as that of the first embodiment.

10 According to the drive pulse of the third embodiment, the third ink drop is discharged at an interval nearly equal to $1.5T_c$ after the second ink drop, the third ink drop canceling out the residual pressure vibration.

15 Next, the drive pulse of the fourth embodiment is explained with reference to Fig. 22. According to the drive pulse of the fourth embodiment, the interval between the first ink drop discharged by the drive pulse P1 and the second ink

20 drop discharged by the drive pulse P2 is set to $2.5T_c$ (i.e., $n=2$), the interval between the second ink drop discharged by the drive pulse P2 and the third ink drop discharged by the drive pulse P3 is set to $2T_c$, and the interval between the third ink

25 drop discharged by the drive pulse P3 and the fourth

-49-

ink drop discharged by the drive pulse P4 is set to $2T_c$. Here, the head structure is the same as that of the first embodiment.

In this drive pulse, the second ink drop
5 is discharged at an interval nearly equal to $2.5T_c$ after the first ink drop, the second ink drop canceling out the residual pressure vibration.

The first through the fourth embodiments of the present invention provide drive pulses (i.e.,
10 a drive signal for forming a large ink drop) that widen the available voltage range, within which voltage range operations are stable without excessive vibration due to the residual pressure.

Nevertheless, from the viewpoint of
15 merging all the four ink drops, the second embodiment is more preferred to the fourth embodiment, because the total interval from the first ink drop to the fourth ink drop of the fourth embodiment is $6.5T_c$ that is longer than the second
20 embodiment where the total interval is $5.5T_c$.

Next, the drive pulse of the fifth embodiment is explained with reference to Fig. 23. According to the drive pulse of the fifth embodiment, the first ink drop is discharged by "pull and
25 strike", that is, the pressurized ink chamber 46 is

-50-

first expanded, and then contracted to discharge the first ink drop. For this purpose, a wave element b wherein the voltage falls from a reference voltage V_{ref} , and a wave element c wherein the expansion state of the pressurized ink chamber 46 is maintained are inserted before the drive pulse P1.

In the fifth embodiment, the interval between the first ink drop discharged by the drive pulse P1 and the second ink drop discharged by the drive pulse P2 is set to $1.5T_c$, the interval between the second ink drop discharged by the drive pulse P2 and the third ink drop discharged by the drive pulse P3 is set to $2T_c$, and the interval between third ink drop discharged by the drive pulse P3 and the fourth ink drop discharged by the drive pulse P4 is set to $2T_c$.

In this drive pulse sequence, the second ink drop is discharged at an interval nearly equal to $1.5T_c$ after the first ink drop, the second ink drop canceling out the residual pressure vibration.

The "pull and strike" has pros and cons. Drawbacks include the first ink drop becoming small due to the meniscus being once drawn back when the pressurized ink chamber is expanded, and there being difficulties in controlling because change of ink

-51-

drop speed to voltage change is great (i.e., inclination of the voltage characteristic is steep) due to piled up pressure of expansion and contraction. Advantages include the total wave time
5 being short because time to return to the reference voltage is not needed, and the injection direction being correctly maintained with the meniscus being drawn back once even when the nozzle is dirty.

As described above, the present invention
10 can be applied to the case where the first ink drop is discharged by "pull and strike".

Next, the drive pulse of the sixth embodiment of the present invention is explained with reference to Fig. 24. According to the drive
15 pulse of the sixth embodiment, the pressurized ink chamber is first expanded, and then contracted for discharging the first ink drop; however, the contraction volume is greater than the expansion volume, which provides discharging in the middle of
20 "pull and strike" (the fifth embodiment) and "push and strike" (the first through the fourth embodiments). Specifically, the wave element b for expanding the pressurized ink chamber 46, and the wave element c for holding the expansion state of
25 the pressurized ink chamber 46 are inserted before

-52-

the drive pulse P1, wherein the wave form b starts falling from a voltage V_a that is lower than the reference voltage V_{ref} .

The intervals between the drive pulses P1, P2, P3 and P4 are the same as the fifth embodiment.

Accordingly, the second ink drop is discharged at an interval nearly equal to $1.5T_c$ after the first ink drop, the second ink drop canceling out the residual pressure vibration.

The sixth embodiment of the present invention is characterized by discharging a large ink drop, while retaining the advantages of the fifth embodiment. In order to enlarge the ink drop volume M_j with a small number of pulses, the second embodiment (wherein the first ink drop is discharged by "push and strike"), and the sixth embodiment (wherein the first ink drop is discharged "pull and strike" where the contraction volume is greater than the expansion volume) are advantageous.

Next, the interval between the drive pulse for discharging the first ink drop and the second drive pulse for discharging the second ink drop is explained with reference to Fig. 25. Fig. 25 shows how the ink drop volume M_j increases as the number of pulses is increased in the case of the drive

-53-

pulse of the second embodiment ("push and strike")..
Each time a pulse was transmitted, the total
"discharge volume M_j " was measured, and the volume
of each drop was obtained by calculating the
5 difference, i.e., the increment.

The reason why the volume of the second
ink drop is small is that the pressurized ink
chamber 46 was not sufficiently refilled with ink
after discharging the first ink drop of great volume,
10 and the meniscus was drawn back. Since the meniscus
was restored as it proceeded to the third ink drop
and the fourth ink drop, the volumes of the third
and the fourth ink drops became great.

Fig. 26 shows the frequency
15 characteristics of a pulse in the case of "push and
strike" for reference. If the discharge interval
becomes short (i.e., the frequency is high), since
the meniscus is not restored, the ink drop volume M_j
tends to be small as clearly seen from Fig. 26. The
20 result shown by Fig. 25 (the second ink drop volume
being small) is largely attributed to the meniscus
not being restored in time.

For a given amount of energy, if the ink
drop volume M_j is made small, the ink drop speed V_j
25 becomes great. Accordingly, in the case of the

-54-

second embodiment ("push and strike") and the sixth embodiment ("pull and strike"), as for the second ink drop, the ink drop speed V_j tends to become high, because the meniscus is drawn back, and the ink drop
5 volume M_j is small as shown in Fig. 25.

In order to prevent the ink drop speed from becoming excessively high, the second ink drop is discharged at the interval nearly equal to $T_c \times (n+1/2)$ after the first ink drop as practiced in the
10 drive pulse of the second embodiment and the drive pulse of the sixth embodiment. In this manner, a wider range wherein stable discharge is available is obtained.

Next, the ink drop speed of an ink drop
15 following a preceding ink drop is explained with reference to Fig. 27 and Fig. 28. The ink drop speed V_j and the ink drop volume M_j of the drive pulse of the first embodiment were measured by making a voltage V_{p2} of the drive pulse P2 into a parameter,
20 V_{p2} being shown in Fig. 27. The results are shown in Fig. 28.

As seen from Fig. 28, as the voltage of the drive pulse P2 is raised, the residual pressure vibration is cancelled out little by little, and
25 both the ink drop speed V_j and the ink drop volume

-55-

Mj become small. Further, the second ink drop was not discharged at voltages lower than 12 V, and the second ink drop starts to be discharged at slightly above 12 V; however, the injection direction was bent (deflected from the downward direction). This is because the second ink drop somehow floated, rather than flew, due to the voltage of the drive pulse P2 being too low, which resulted in the third and subsequent ink drops merging at a deflected angle. Accordingly, it was determined that a certain amount of speed is required for the second ink drop.

In order for the direction bend not to occur, a speed higher than 2 m/s was required for the second ink drop. This was determined by measuring the time required for the second ink drop to reach 1 mm ahead without discharging the third and the fourth ink drops.

On the other hand, making the second ink drop speed too high produces a satellite that is separated from the main ink drop, which is not desirable. Thus, the highest speed for the second ink drop is limited. In the case of this embodiment, when the ink drop speed exceeded 7 m/s, a satellite was produced.

When the whole drive pulse shown in Fig.

-56-

27 was shifted upward (given a voltage offset), and the voltage V_{p2} of the drive pulse P2 was further increased, discharge had a tendency to become unstable from the vicinity where a satellite was
5 produced by the second ink drop.

Accordingly, as for the ink drop that is discharged at an interval of $T_c \times (n+1/2)$ to the preceding ink drop, it is desirable that the ink drop speed be set higher than 3 m/s, and lower than
10 a speed for ink drops to dissociate (fail to merge), producing a satellite.

Thus, by setting the ink drop speed V_j of the ink drop that is discharged at the interval nearly equal to $(n+1/2) \times T_c$ after the preceding ink
15 drop higher than 3 m/s, soiling of the nozzle and unstable operations due to poor discharge are prevented from occurring. In other words, the ink drop speed V_j tends to become low if the interval is set nearly equal to $(n+1/2) \times T_c$, the low speed
20 causing the nozzle to become soiled, and for this reason, a higher voltage is set, at which voltage the nozzle does not become soiled. Further, the voltage is set lower than a voltage at which a satellite is produced. In this manner, stable
25 discharge of ink drops is obtained.

-57-

Next, the drive pulse of the seventh embodiment of the present invention is explained with reference to Fig. 29. The drive pulse according to the seventh embodiment contains the first through
5 fifth drive pulses P1 through P5 for discharging the first ink drop through the fifth ink drop, respectively. The intervals between P1 and P2, and between P3 and P4 are set at $1.5T_c$; and the intervals between P2 and P3, and between P4 and P5
10 are set at $2T_c$.

Thus, five ink drops are discharged, wherein the second ink drop and the fourth ink drop are discharged at the interval $1.5T_c$ after the respective preceding ink drops. The present
15 invention is effective, especially when four or more ink drops are discharged and merged, including the above-mentioned embodiments.

Further, the specific vibration cycle T_c of the pressurized ink chamber according to the
20 embodiments of the present invention was about 6.5 μs , and in the case that ink drops are discharged at intervals of nT_c , it is desirable that $n=3$ or greater, i.e., at 19.5 μs intervals at least. With reference to the conventional example as shown by
25 Fig. 40, a peak is still present at about 20 μs

-58-

intervals, the peaks being due to the influence of the residual pressure because of insufficient damping. However, this is better than repeatedly discharging ink drops at intervals of $2T_c$.

5 An example wherein three ink drops are discharged is considered. The third ink drop is made to start $2 \times 19.5 = 39$ μ s after the first ink drop. Suppose that the speed of the first ink drop is set at 6 m/s. For the third ink drop to catch up to the
10 first ink drop while traveling the 1 mm distance, a speed of 7.8 m/s is required. In the case of four ink drops, the fourth ink drop pursues after $3 \times 19.5 = 58.5$ μ s, and the speed of the fourth ink drop has to be 9.2 m/s at least. In order to raise the
15 speed, the pressure has to be raised, and the raised pressure narrows the margin for stable discharge due to the residual pressure vibration. In the case of five ink drops, the fifth ink drop starts flying 78 μ s after the first ink drop, and the speed of the
20 fifth ink drop has to be 11.3 m/s at least. Reliable and stable discharge at this speed is hard to achieve.

 The seventh embodiment, containing $1.5T_c$ intervals that have the vibration suppression
25 effects, as described above solves this problem,

-59-

where the fifth ink drop is discharged about 48.8 μ s after the first ink drop successfully merging with the preceding ink drops without generating excessive pressure vibration.

5 Next, the drive pulse of the eighth embodiment of the present invention is explained with reference to Fig. 30. The drive pulse according to the eighth embodiment contains a wave P_e having a wave element e for damping after discharge of the
10 last ink drop, wherein the second ink drop is discharged at the $1.5T_c$ interval.

 The pressurized ink chamber 46 is contracted by the rising edge of P_e , the ink drop is discharged, the pressurized ink chamber 46 expands
15 by the specific vibration, and after a period of about the $T_c/2$ interval the pressurized ink chamber 46 tends to be contracted by the specific vibration. At this moment, the wave element e for damping is applied to the pressurized ink chamber 46 such that
20 the tendency of the pressurized ink chamber 46 to contract is counter-balanced by the expanding power of the wave element e . That is, when the pressurized ink chamber 46 contracts again, the wave element e expands the pressurized ink chamber 46. In this
25 manner, the vibration of the pressurized ink chamber

-60-

46 is suppressed. That is, the wave element e carries out pressure damping of the last ink drop, the speed of which tends to be set high for merging.

As described above, by providing the
5 discharge interval of $T_c (n+1/2)$ cycle, and the damping wave element e within the T_c cycle just behind the last ink drop, the pressure vibration is suppressed, and stable ink drop discharge is carried out in a wide operational range.

10 Next, the drive pulse of the ninth embodiment of the present invention is explained with reference to Fig. 31 and Fig. 32. Here, Fig. 32 is an expanded view of an area marked as Pf in Fig. 31. The drive pulse according to the ninth
15 embodiment includes a waveform Pf that contains a wave element f for damping the residual pressure vibration within the T_c (the pressurized ink chamber specific vibration cycle) after the last ink drop discharge, in addition to the second ink drop being
20 discharged at the $1.5T_c$ interval, and the wave element e mentioned above being provided.

The damping drive within the interval T_c immediately after the discharge is highly effective in suppressing the pressure vibration due to the
25 specific vibration cycle T_c as compared with usual

-61-

damping. Specifically, the wave element f for damping is for contracting the pressurized ink chamber 46, and is applied to the pressurized ink chamber 46 when the pressurized ink chamber 46 tends to expand by the specific vibration after the pressurized ink chamber 46 is once contracted and discharges the ink drop. In this manner, the vibration of the pressurized ink chamber 46 is suppressed. This is effective for suppressing the pressure of the last ink drop that tends to be discharged at a high speed for merging.

As described above, by providing the discharge interval of $T_c (n+1/2)$ cycle, and the damping wave element within the T_c cycle just behind the last ink drop, the pressure vibration is suppressed, and stable ink drop discharge is carried out in a wide operational range.

Next, gradation printing is explained with reference to Figs. 33 through 38. Concerning the embodiments described above, descriptions are made as to how a large ink drop is formed by stably discharging two or more ink drops. Below, an example for performing gradation printing by switching a drive pulse within 1 printing cycle is explained.

First, the wave generation unit 91 (ref.

-62-

Fig. 6) generates and outputs a drive pulse as shown in Fig. 33. The drive pulse includes six drive pulses P20 through P25, wherein the drive pulse P24 contains a pressure-suppression signal Pf that is provided within the specific vibration cycle Tc of the pressurized ink chamber 46.

Figs. 34 through 36 show drive pulses applied to the piezoelectric device for a large ink drop, a medium-sized ink drop, and a small-sized ink drop, respectively, corresponding to gradation data from the main control unit 73. Further, Fig. 37 shows the drive pulse when no printing is performed in a printing cycle.

Switching signals shown in Figs. 34 through 37 indicate the timing of switching, but do not represent absolute voltage values. The switching signal is defined as "low is active", i.e., when the voltage of a switching signal is low, an analog switch ASm is turned on.

When forming a large ink drop, rising edges of the drive pulses P21 through P24 are used for discharging four ink drops as shown in Fig. 34. The interval between the first ink drop (discharged by the drive pulse P21) and the second ink drop (discharged by the drive pulse P22) is set to $1.5T_c$,

-63-

and the interval between the second ink drop and the third ink drop (discharged by the drive pulse P23) is set to $1.5T_c$. As mentioned above, the pressure-suppression signal Pf is prepared within the T_c interval to P24 for the fourth ink drop.

This effect is the same as in the above-mentioned embodiments, that is, the resonance of the specific vibration cycle T_c is properly suppressed, and a large ink drop is stably formed.

Fig. 35 shows the waveform for forming a medium-sized ink drop, wherein the drive pulse P23 (the same as the third ink drop of the large ink drop) is used. Nevertheless, since it is necessary to raise the voltage by an inclination that does not cause ink discharge at the beginning of a printing cycle, the rising wave element a1 of the pulse P20 is used. Here, the inclination of the wave element a1 is set such that ink is not discharged.

Fig. 36 shows the drive signal for forming a small-sized ink drop, containing the drive pulse 25 that is not used when forming the large ink drop. Although a part of the drive pulse for forming the large ink drop can also be used, an independent wave element is used for forming the small-sized ink drop 25 in this example.

-64-

Thus, according to the present invention, the time required for forming a large ink drop is shortened, which enables incorporating another wave without reducing the printing speed (i.e., without
5 extending the printing cycle). Although selecting one or more drive pulses from a drive pulse sequence containing two or more drive pulses for forming two or more sizes of ink drops has been in practice, it is difficult for a printing cycle to contain a great
10 number of drive pulses for forming different sizes of ink drops where high printing speed is required. The present invention solves this problem as described above.

With reference to Fig. 37, the switching
15 signal for a non-printing cycle stays high such that an equi-potential level is provided (i.e., no pulses) except for the last stage of the printing cycle, where the switching signal shifts to low. This is for turning on the analog switch ASm, and
20 for recharging the piezoelectric device such that charges leaked from the piezoelectric device are restored, and potential that may have varied is realigned. Although the recharging pulse is provided at the last of the drive pulses in this example, the
25 recharging pulse can be provided at another place.

-65-

In this manner, when the piezoelectric device serves as the pressure generating means, the potential displacement by charge leaking from the piezoelectric device is prevented from occurring by providing a section where the switch means are made into the ON state. In this manner, reproducible operations and stable ink discharge are realized.

Further, the drive pulse for the non-printing cycle can take a form as shown in Fig. 38, wherein a voltage that does not cause an ink drop to be discharged is applied. This is for vibrating the meniscus of a non-printing channel such that ink dryness of the nozzle is prevented from occurring. Further, since the analog switch is turned on, charge that may have leaked can be restored. Furthermore, depending on the length of the wave, a recharging period can be prepared after raising the voltage and before dropping the voltage.

[Effect of the Invention]

As described above, according to the image formation apparatus of the present invention, at least one ink drop other than the last ink drop is discharged at an interval nearly equal to $(n+1/2) \times T_c$ after the preceding ink drop. In this manner, the pressure vibration of the pressurized ink chamber is

-66-

prevented from becoming excessive. The rule is not applied to the last ink drop such that a large ink drop can be formed. The ink drop volume M_j can range widely. Stable ink drop discharge is realized. As a
5 result thereof, a high-definition image can be formed at high speed.

Further, the present invention is not limited to these embodiments, but various variations and modifications may be made without departing from
10 the scope of the present invention.

The present application is based on Japanese Priority Application No. JPA 2003-183158 filed on June 26, 2003, with the Japanese Patent Office, the entire contents of which are hereby
15 incorporated by reference.